

# Bottle Jacks

## 2-110 Ton Capacity

Portable hydraulic power in a rugged, reliable unit.



- Choose from this complete line of premium-quality, standard bottle jacks. Ideal for use in any number of industrial lifting and pushing applications.
- The 9110B, 9015B, 9022B and 9033B feature a beveled base which allows the jack to “follow” the load, reducing the chance of dangerous side-loading.
- Many jacks feature screw extensions and all can be used in the vertical, angled or horizontal positions.
- Serrated or contoured saddles help stabilize the load for a safer lift.
- All jacks meet ASME B30.1 standards and carry the Power Team Marathon Lifetime Warranty.
- 110 ton jack features dual pumps for time-saving two-speed operation.



### ORDERING INFORMATION

See current price list for shipping weights.

Cap. Tons	Stroke (mm)	Order Number	Retracted Height Min. (mm)	Length of Screw Ext. (mm)	Height with Screw Ext. (mm)	No. Pump Strokes to Ext. piston 25 mm	Saddle Dia. (mm)	Base Size Beveled Base: † (mm)	Pump Handle Length (mm)	Handle Effort at Rated cap. (kg)	Carry Handle	Product Weight (kg)
2	114	9002A	181	49	344	5	25	110 x 65	311	34	No	2.2
3	114	9003A	191	60	365	10	29	114 x 72	489	20.4	No	2.6
5	121	9005A	200	70	391	12	35	132 x 76	545	24.9	No	3.6
8	121	9008A	200	70	391	18	38	152 x 89	605	34	No	5.5
12	149	9112A	241	79	470	26	48	165 x 106	605	27.2	Yes	7.9
15	156	9015B	230	110	495	27	60	130 x 140†	700	40.8	No	8.3
20	159	9120A	270	40	429	22	51	183 x 129	800	31.7	Yes	12.9
22	156	9022B	240	110	505	36	60	165 x 160†	700	40.8	Yes	10.7
30	159	9030A	279	—	438	35	60	192 x 141	1,000	22.7	Yes	18.7
33	143	9033B	240	100	483	56	65	184 x 176†	700	39.9	No	14.5
50	171	9050A	305	—	476	35	76	237 x 187	1,000	38.6	Yes	35.4
110	156	9110B	300	—	456	40/160‡	111	339 x 291	700	35.8	Yes	70

‡ 2 Speed: Rapid advance=40 strokes; Lift mode=160 strokes