

# Low Profile Bottle Jacks

## 12, 20 & 30 Ton Capacity

The right choice for those lower clearance jobs.



- All the quality, features and lifting capacity of the standard jacks in short form. The 12-ton and 20-ton models feature screw extensions for added versatility.
- All jacks meet ASME B30.1 standards and carry the Power Team Marathon Lifetime Warranty.
- All jacks operate both vertically and horizontally for use in a variety of lifting, pushing and spreading applications.

### ORDERING INFORMATION

See current price list for shipping weights.

Cap. Tons	Stroke (mm)	Order Number	Retracted Height Min. (mm)	Length of Screw Ext. (mm)	Height with Screw Ext. (mm)	No. Pump Strokes to Ext. piston 25 mm	Saddle Dia. (mm)	Base Size (mm)	Pump Handle Length (mm)	Handle Effort at Rated cap. (kg)	Carry Handle	Product Weight (kg)
12	95	9012A	171	76	343	26	48	165 x 106	605	27.2	Yes	6.4
20	86	9020A	181	40	305	22	51	183 x 129	800	31.8	Yes	10.1
30	79	9130A	181	—	260	35	60	192 x 141	1,000	22.7	Yes	13.7

‡ 2 Speed: Rapid advance ≈ 40 strokes; Lift mode ≈ 160 strokes