

Retaining Ring Pliers

714
Fed. Spec.:
GGG-P-480

7313

7123K

7053K
internal &
external
plier, 4 sizes
of tips.

7406K

Fed. Spec.: GGG-P-480-E

External		Internal		Convertible
No. 0200	No. 7301	No. 0100	No. 7300	No. 1120
No. 0400		No. 0300		No. 1320
No. 0600		No. 0500		No. 1340
				No. 1125*
				No. 1345*
				No. 1131**
				No. 1329**
				No. 1349**

* 45° Angled Tips ** 90° Angled Tips

Horseshoe lock ring plier

For removing horseshoe lock rings used on hydraulic brakes, differentials, etc. Plier is 203 mm long; max. spread: 23.8 mm

No. 714 – Horseshoe lock ring plier. Wt., 170 g.

No. 7313 – External snap ring plier easily removes snap rings used to retain bearings on shafts. Max. spread: 36.5 mm.

Retaining ring plier kits

Choose from four sets; internal ring, external ring and convertible pliers for either internal or external rings.

No. 7053K – Replaceable tip pliers kit. This versatile kit contains (1) internal and (1) external pliers with (8) tip sets. Two sets each: .9 mm dia. 90° bend, 1.2 mm dia. straight, 1.2 mm dia. 90° bend, 1.8 mm dia. straight. Recommended for 6.4-51 mm rings. Packaged in plastic storage case. Wt., 340 g.

No. 15702 – Replaceable tip kit (only) for No. 7053K.

No. 7123K – Convertible pliers kit. Contains No. 1120 (.9 mm dia./straight tip) and No. 1340 (1.8 mm dia./straight tip). Each pliers “converts” to handle both internal and external rings. Packaged in a reusable plastic storage case. Wt., 340 g.

No. 7125K – Convertible pliers kit. Contains No. 1125 (.9 mm dia./45° bent tip) and No. 1345 (1.8 mm dia./45° bent tip). Each pliers “converts” to handle both internal and external rings. Packaged in a reusable plastic storage case. Wt., 340 g.

No. 7406K – Professional pliers kit. Contains (6) retaining convertible pliers to handle both internal and external rings from 6.4-51 mm. Includes straight and 90° off-set pliers with .9 mm, 1.2 mm and 1.8 mm tip diameters. Includes Nos. 1120, 1131, 1320, 1329, 1340 and 1349. Packaged in an impact resistant storage case. Wt., 0.9 kg.

Replacement tips for 7300 and 7301 pliers:

No. 209201 – Replacement tips (pr.) for the 7300 and 7301 pliers. Wt., 57 g.

Retaining Ring Pliers Selection Guide

Plier No.	Tip Bend	Tip Size Dia. (mm)	For Int'l Rings* Bore Dia. (mm)	For External Rings* Shaft Dia. (mm)
0100	Str.	.97	9.5 - 26	—
0200	Str.	.97	—	6.4 - 22
0300	Str.	1.78	27 - 44.5	—
0400	Str.	1.78	—	24 - 36.5
0500	Str.	2.29	46 - 89	—
0600	Str.	2.92	—	38 - 89
7300	Str.	3.05	78 - 152	—
7301	Str.	3.05	—	38 - 165
Convertible Pliers				
1120	Str.	.97	9.5 - 14	6.4 - 17
1125	45°	.97	9.5 - 14	6.4 - 17
1131	90°	.97	9.5 - 14	6.4 - 17
1320	Str.	1.19	16 - 26	17 - 22
1329	90°	1.19	16 - 26	17 - 22
1340	Str.	1.78	27 - 44.5	24 - 36.5
1345	45°	1.78	27 - 44.5	24 - 36.5
1349	90°	1.78	27 - 44.5	24 - 36.5

Always wear Safety Goggles when using Pliers

* Capacities are shown for basic style rings.