
































# Hydraulic Fittings

700 bar

Power Team's fittings include a wide range of types and sizes. Ideal for many hydraulic applications.

HOSES, FITTINGS, GAUGES

	Order No.	Description
	9190	Hyd. tubing. 3/8" O.D. x 21/32" wall, 15.3 m. (10 pieces 1.53 m long.) Wt., 5.5 kg.
	9670	Tee adapter. For installing gauge between pump and hose coupling. Has 1/4" and 3/8" NPTF female and 3/8" NPTF male ports. Wt., 226 g.
	9671	Double tee adapter. Permits use of more than one cylinder in series with one pump. Three 3/8" NPTF female ports. Wt., 453 g.
	9672	Service tee. Two 3/8" NPTF female internal, one 3/8" NPTF male external. Wt., 272 g.
	9673*	Swivel connector. 3/8" NPSM male, 1/4" NPSM female. Wt., 91 g.
	9674	Male connector. 43 mm long, 1/4" x 3/8" NPTF. Wt., 91 g.
	9675*	Swivel connector. 3/8" NPTF male, 3/8" NPSM female. Wt., 91 g.
	9676*	Swivel connector. 1/4" NPTF male, 3/8" NPSM female. Wt., 91 g.
	9677*	45 swivel connector. 3/8" NPTF male, 3/8" NPSM female. Wt., 136 g.
	9678	45 fitting. Used when mounting gauge at an angle on connection such as 9670. Male and female 1/4" NPTF ends. Wt., 136 g.
	9679	Connector. 1/4" NPTF female and 3/8" NPTF male. Wt., 45 g.
	9680	Coupling. Both ends 3/8" NPTF female. Wt., 91 g.
	9681	Street elbow. Male and female 3/8" NPTF ends. Wt., 136 g.
	9682	Male connector. 43 mm long, 3/8" NPTF male ends. Wt., 45 g.
	9683	Male connector. 57 mm long, 3/8" NPTF male ends. Wt., 91 g.
	9684	Male connector. 57 mm long, 1/4" NPTF male ends. Wt., 91 g.

	9685	Coupling. 1/4" NPTF female and 3/8" NPTF female. Wt., 91 g.
	9686	90 elbow. 3/8" NPTF female ends. Wt., 181 g.
	9687	Pipe plug. Heat-treated, 3/8" NPTF. Wt., 45 g.
	9688	Pipe plug. Heat-treated, 1/4" NPTF. Wt., 45 g.
	9689	Connector. 1/4" NPTF male and 3/8" NPTF female. Wt., 91 g.
	9690	Male connector. 43 mm long, 1/4" NPTF male ends. Wt., 45 g.
	9692	Straight connector. 3/8" tube x 3/8" male NPTF. Wt., 0.2 lb.
	9693	90 elbow. 3/8" tube x 3/8" male NPTF. Wt., 91 g.
	9694	45 elbow. 3/8" tube x 1/4" male NPTF. Wt., 91 g.
	9695	Tee. 3/8" tube. Wt., 136 g.
	9696	Male run tee. 3/8" tube x 1/4" male NPTF. Wt., 136 g.
	9697	Male branch tee. 3/8" tube x 1/4" male NPTF. Wt., 136 g.
	9698	Cross. 3/8" tube. Wt., 181 g.
	9699	45 gauge fitting. 3/8" NPTF male and female, and 1/4" NPTF female at 45. Wt., 272 g.
	9705	Fitting, swivel. 3/8" NPTF male to 3/8" NPTF female. 90 fitting with internal 370 micron screen. May be rotated 360 about male thread axis.

**NOTE:** Power Team hydraulic fittings are intended for use with our high pressure hydraulic products and are suitable for use at max. working pressures of 700 bar unless otherwise noted.

**CAUTION:** On part numbers 9673, 9675, 9676 and 9677 the female swivel end of these adapters is a straight pipe thread (NPSM) with a 30° seat. All male pipe fittings that are used with these female swivel adapters must have an internal 30° seat in order to effect a proper seal. All Power Team male fittings are manufactured with a 30° seat except 9687 and 9688.