

Sidewinder Mini Jacks

5-20 Ton Capacity

The Sidewinder Mini Jacks may be small (fits in the palm of your hand) but don't let their compact size fool you. They deliver 5, 10 & 20 tons of lifting force.



- Retracted height of just 63.5 mm for the smallest jack and 130.2 mm for the 20 ton, allows you to slip this jack into the narrowest of crevices.
- Jacks operate either horizontally or vertically. Handles function in line with base for easier use in confined spaces.
- The perfect addition to any toolbox, this remarkable little jack has multiple uses that are limited only by your imagination. Use it as a jack or a spreader. Use it to turn your mechanical gear puller (puller capacity must match jack capacity) into a hydraulic puller. Use it vertically or horizontally in limited clearance.
- All jacks meet ASME B30.1 standards and carry the Power Team Marathon Lifetime Warranty.



JACKS

ORDERING INFORMATION

See current price list for shipping weights.

| Cap. Tons | Stroke (mm) | Order Number | Retracted Height Min. (mm) | Max Height (mm) | No. Pump Strokes to Ext. piston | Saddle Dia. (mm) | Base Size (mm) | Pump Handle Length (mm) | Handle Effort at Rated capacity (kg) | Carry Handle | Product Weight (kg) |
|-----------|-------------|--------------|----------------------------|-----------------|---------------------------------|------------------|----------------|-------------------------|--------------------------------------|--------------|---------------------|
| 5 | 19 | 9105A | 63.5 | 85.7 | 30 | 29 | 73.8 Dia. | 239.7 | 25.9 | No | 1.9 |
| 5 | 38 | 9205A | 88.9 | 130.2 | 38 | 29 | 73.8 Dia. | 239.7 | 25.9 | No | 2.4 |
| 10 | 30 | 9210A | 120.7 | 149.2 | 36 | 42.1 | 109.9 Dia. | 440.1 | 28.1 | No | 5.5 |
| 20 | 30 | 9220A | 130.2 | 160.3 | 46 | 52.8 | 119.9 Dia. | 604.8 | 35.0 | No | 8.0 |