

Hydraulic Tool Accessories

Optional accessories for use with CC5, CC10 & CC25 hydraulic clamps

Swivel Caps		Threaded Adapters		Pushing Adapters		Pushing Adapters		Pushing Adapters		V Pushing Adapters		Pushing Adapters	
5/10 ton 350144*	25 ton 350145	10 ton 38597	25 ton 38953	10 ton 28228**	25 ton 28229**	10 ton 201923**	25 ton 34510**	10 ton 201454**	25 ton 34511**	10 ton 34806**	25 ton 34807**	5 ton 309874*	
A-34.9 mm	A-50.8 mm	A-1 - 8	A-1 1/4-7	A-60.3 mm	A-73 mm	A-79.4 mm	A-82.6 mm	A-79.4 mm	A-82.6 mm	A-66.7 mm	A-79.4 mm	A-51.6 mm	A-70.6 mm
B-19.1 mm	B-25.4 mm	B-1 - 8	B-1 1/2-16	B-1 - 8	B-1 1/4-7	B-57.2 mm	B-66.7 mm	B-57.2 mm	B-66.7 mm	B-1 - 8	B-1 1/4-7	B-70.6 mm	B-15.9 mm
		C-19.1 mm	C-69.9 mm	C-38.1 mm	C-44.5 mm	C-137 mm	C-149 mm	C-137 mm	C-149 mm	C-38.1 mm	C-44.5 mm		
		D-50.8 mm	D-111 mm			D-12.7 mm	D-19.1 mm	D-19.1 mm	D-25.4 mm	D-25.4 mm	D-31.8 mm		
						E-1 - 8	E-1 1/4-7	E-1 - 8	E-1 1/4-7				

* May be used with CC5

** Must be used with a threaded adapter.

Punch/Die Sets for HP20 & HP35 hydraulic punches

Punch Size (mm)	Punch Style	For use with HP20 Hydraulic Punch				For use with HP35 Hyd. Punch	
		Punch Number	Flat Die No.	Bevel Die No.	Coupling Nut No.	Punch/w Flat Die Set	Punch/w Bevel Die Set
6.4	Round	251970	251983	—	252001	—	—
7.9		251971	251984	—	252001	PD313	—
9.5		251972	251985	251996	252001	PD375	PD375B
11.1		251973	251986	251997	252001	PD437	PD437B
13.5		251974	251987	251998	252001	PD531	PD531B
14.3		251975	251988	251999	252001	PD562	PD562B
17.5		251976	251989	—	252001	PD688	—
19.8		251977	251990	—	252002	PD781	—
20.6		251978	251991	—	252002	PD812	—
12.7		Square	251979	251992	—	252002	—
13.5	251980		251993	—	252002	—	—
6.4 x 19	Obround	251981	251994	—	252002	—	—
9.5 x 19		251982	251995	—	252002	—	—

Punch Size (mm)	INCHES		MM	
	Hole Dia.	Bolt	Hole Dia.	Bolt
6.4	1/4	#10	6.3	—
7.9	5/16	1/4	7.9	—
9.5	3/8	5/16	9.5	M8
11.1	7/16	3/8	11.2	M10
13.5	17/32	7/16	13.5	M12
14.3	9/16	1/2	14.3	—
17.5	11/16	5/8	17.5	M16
19.8	25/32	—	19.8	M18
20.6	13/16	3/4	20.6	—

Typical 20 ton style tooling



Accessories for HP20 hydraulic punch

- No. HP20FS** - Optional foot switch mounted in foot switch guard. Supplied with 3 m cord and male remote connector. Wt., 0.9 kg.
- No. HP20HS** - Replacement handswitch. Supplied with 3 m cord and male remote connector. Wt., 0.9 kg.
- No. 252000** - Optional coupling nut wrench. Makes punch/die changes easier without "rounding-off" coupling nuts. Wt., 0.23 kg.