

Pressure Reducing Valves

- 420 bar Maximum Pressure (Most Valves)
- Filtration Requirements – 25 Microns or better
- Hardened working parts for maximum durability
- Adjustable, preset and tamperproof versions available

Part Number	Symbol	Type	Cavity	Spring (bar)	Flow (lpm)	Cat. Page	List Price
REDUCING WITH RELIEVING FUNCTION – Direct Acting							
C02A3CZN		DIRECT ACTING SPOOL	CAV02-3	5-40	20	434	\$159
C02A3EZN			CAV02-3	25-75	20	434	\$159
C02A3GZN			CAV02-3	50-150	20	434	\$159
C3A025ZN			3G	20-100	40	436	\$228
REDUCING WITH RELIEVING FUNCTION – Pilot Operated							
C04B3HZN		PILOT OPERATED SPOOL	CAV04-3	10-210	120	430	\$189
C04B3MZN			CAV04-3	10-350	120	430	\$181
C2B125ZNMK2			3G	10-210	120	8.74	\$302
C2A125ZNMK2			3G	10-350	120	8.74	\$303
C06B3HZN			CAV06-3	10-210	200	432	\$271
C06B3MZN			CAV06-3	10-350	200	432	\$260
PROPORTIONAL PRESSURE REGULATOR – Increasing Pressure with Current							
GP0130		BOTTOM	54-1	0-22	1.9	170	\$203
GTP02340201N		SIDE	CAV02-3	0-10	19	172	\$331
GTP02340201N			CAV02-3	0-21	19	172	\$351